

## Adherent 1125

### Adhesion Promoter

#### DESCRIPTION

Adherent 1125 is a modified silane, designed primarily as an adhesion and water resistance promoter for paints and adhesives. This product can also be used as a primer.

#### TYPICAL PROPERTIES

These values are used as reference. For detailed product specifications, please contact our distributor or sales department.

Composition	: mixture of epoxy methoxy silane and resin
Appearance	: clear viscous liquid
Non-volatile content	: above 86%
Specific gravity	: 1.16 - 1.20

#### FEATURES

- To improves adhesion in a paint.
- To improves adhesion of an adhesive.
- Can act directly as a primer.
- To improves water resistance of paints and adhesives.

#### APPLICATIONS

- acrylic coatings
- alkyd coatings
- polyester coatings
- polyurethane coatings
- epoxy resin

#### DOSAGE & USE

- As primer, dilute with polar solvent (methyl alcohol or propylene glycol monmethyl ether) to 10% before use.
- As additive, 0.5 - 3.0% based on total formulation. It can added at last dilute stage.

#### PACKAGE

Net Weight: 180 kg / 25 kg

#### STORAGE

- Keep away form sources of ignition and heat.
- Keep container tightly closed in a dry and well-ventilated place.
- Stored between 0°C and 40°C (use it when temperature goes back to 25°C).
- Packaging not to be exposed directly under heat radiation.

#### SAFETY

- As it contains a solvent, the product requires special care in handling.
- Avoid any eye and skin contact.
- For further information please check MSDS.

The data presented is the result of careful and extensive research. However, since the actual conditions under which the materials may be used are beyond our control, no warranty of any kind, expressed or implied, concerning the use of the products is made.