

Defom 3500

Defoamer

DESCRIPTION

Defom 3500 is a silicone-free bubble releasing and anti-foaming agent for solvent-based and solvent-free systems, especially in de-aeration of high filler content wood primer.

TYPICAL PROPERTIES

These values are used as reference. For detailed product specifications, please contact our distributor or sales department.

Composition	: foam destroying polymer, silicone-free
Appearance	: clear liquid
Non-volatile content	: 19 - 21%
Solvent	: aliphatic hydro carbon solvent / butyl glycolate / ethylene glycol monobutyl ether
Specific gravity	: ca. 0.80
Refractive index	: 1.427 - 1.430 (25°C)

FEATURES

- To inhibit foaming in wood primer containing zinc stearate.
- To provide excellent anti-foaming for high filler contents primer.
- It's good air-releasing effect in hand brushing application.
- It's excellent wetting and reduce pinhole in porous substrates such as wood and paper.

APPLICATIONS

- wood primer
- N/C lacquer
- PU primer
- wood coatings

DOSAGE & USE

- 0.1 - 0.5% based on total formulation.
- Add before incorporation of filler to obtain best effect.

PACKAGE

Net Weight: 160 kg / 25 kg

STORAGE

- Keep away from sources of ignition and heat.
- Keep container tightly closed in a dry and well-ventilated place.
- Stored between 0°C and 40°C.

SAFETY

- As it contains a solvent, the product requires special care in handling.
- Avoid any eye and skin contact.
- For further information please check MSDS.

The data presented is the result of careful and extensive research. However, since the actual conditions under which the materials may be used are beyond our control, no warranty of any kind, expressed or implied, concerning the use of the products is made.