

www.deuchem.com



德謙企業股份有限公司 新竹縣湖口鄉新竹工業區光復北路92號 TEL:886-3-5984035 FAX:886-3-5983301

DEUCHEM CO., LTD. 92, Kuang-Fu North Road, Hsinchu Industrial Park, Hu-kou, Hsinchu, Taiwan TEL : 886-3-5984035 FAX : 886-3-5983301

Defom 5800F

Defoamer

DESCRIPTION

Defom 5800F is an aromatic-free defoamer used in solvent-based coatings.

TYPICAL PROPERTIES

These values are used as reference. For detailed product specifications, please contact our distributor or sales department.

Composition	: modified polysiloxane
Appearance	: colorless clear liquid
Non-volatile content	: 2.8 - 3.2%
Solvent	: n-butyl acetate
Specific gravity	: 0.86 - 0.90
Refractive index	: 1.394 - 1.396 (25°C)

FEATURES

- Apply to request aromatic free system, like toy coatings.
- To prevents foaming caused by mechanical forces such as mixing, production and application.
- It can be reducing fish-eye, pinhole and crater defects.
- Good compatibility.

APPLICATIONS

- solvent-based coatings
- toy coatings

DOSAGE & USE

- 0.1 0.7% based on total formulation with sufficient mixing.
- Please check the optimum dosage and test compatibility prior to use.

PACKAGE

Net Weight: 180 kg / 25 kg

STORAGE

- Keep away from sources of ignition and heat.
- Keep container tightly closed in a dry and wellventilated place.
- Stored between 0°C and 40°C.

SAFETY

- As it contains a solvent, the product requires special care in handling.
- Avoid any eye and skin contact.
- For further information please check MSDS.

The data presented is the result of careful and extensive research. However, since the actual conditions under which the materials may be used are beyond our control, no warranty of any kind, expressed or implied, concerning the use of the products is made.