

www.deuchem.com



德謙企業股份有限公司 新竹縣湖口鄉新竹工業區光復北路92號 TEL:886-3-5984035 FAX:886-3-5983301

DEUCHEM CO., LTD. 92, Kuang-Fu North Road, Hsinchu Industrial Park, Hu-kou, Hsinchu, Taiwan TEL: 886-3-5984035 FAX: 886-3-5983301

# Leveling Agent

### DESCRIPTION

Levelol 837 is a fluorocarbon modified polyacrylate flow and leveling agent used in solvent based coatings.

### **TYPICAL PROPERTIES**

These values are used as reference. For detailed product specifications, please contact our distributor or sales department.

| Composition          | : fluorocarbon modified       |
|----------------------|-------------------------------|
|                      | polyacrylate                  |
| Appearance           | : clear to slight hazy liquid |
| Non-volatile content | : 69.0 - 72.0%                |
| Solvent              | : xylene                      |
| Specific gravity     | : ca. 0.98                    |
| Refractive index     | : 1.475 - 1.479 (25°C)        |

## FEATURES

- Good leveling and recoatability.
- No side effect, like intercoat adhesion and surface defect.
- Good substrate wettablility.
- It is light stable, hydrolysis resistant and does not migrate from paint film
- · Good compatability with most solvent and resins.

# APPLICATIONS

solvent-based coatings

## DOSAGE & USE

0.1 - 0.5% based on total formulation. Please test compatibility before use.

## PACKAGE

Net Weight: 200 kg / 25 kg

## STORAGE

- Keep away from sources of ignition and heat.
- Keep container tightly closed in a dry and wellventilated place.
- Stored between 0°C and 40°C.

## SAFETY

- As it contains a solvent, the product requires special care in handling.
- Avoid any eye and skin contact.
- Another information see MSDS.

The data presented is the result of careful and extensive research. However, since the actual conditions under which the materials may be used are beyond our control, no warranty of any kind, expressed or implied, concerning the use of the products is made.