

Levaslip 875

Leveling Agent

DESCRIPTION

Levaslip 875 provides leveling, slip and excellent substrate wetting for non-aqueous coatings.

TYPICAL PROPERTIES

These values are used as reference. For detail product specifications, please contact our distributor or sales department.

Composition	: modified polysiloxane
Appearance	: colorless to slight yellow, clear to slight hazy liquid
Non-volatile content	: 47 - 52%
Solvent	: aromatic hydrocarbon solvent / Butyrolactone
Specific gravity	: 0.98 - 1.01
Reflective index	: 1.457 - 1.460 (25°C)

FEATURES

- Good slip performance.
- It's lower surface tension, improves substrate wetting.
- Fast flowing and leveling when dosage is 0.5% based on total formulation.
- It can be reduce coefficient of friction and improve scratch resistance.
- Excellent compatibility and recoatability.

APPLICATIONS

- N/C lacquer
- 2K PU coatings

DOSAGE & USE

- 0.1 - 0.5% based on total formulation. It is recommended to carry out serial test of Levaslip 875 at various levels to obtain optimum dosage.
- For easy to use, it's better to predilute Levaslip 875 with a suitable solvent.

PACKAGE

Net Weight: 25 kg

STORAGE

- Keep away from sources of ignition and heat.
- Keep container tightly closed in a dry and well-ventilated place.
- Stored between 0°C and 40°C.

SAFETY

- As it contains solvents, the product requires special care in handling.
- Avoid any eye and skin contact.
- For further information please refer to MSDS.

The data presented is the result of careful and extensive research. However, since the actual conditions under which the materials may be used are beyond our control, no warranty of any kind, expressed or implied, concerning the use of the products is made.