

www.deuchem.com



德謙企業股份有限公司 新竹縣湖口鄉新竹工業區光復北路92號 TEL:886-3-5984035 FAX:886-3-5983301

DEUCHEM CO., LTD. 92, Kuang-Fu North Road, Hsinchu Industrial Park, Hu-kou, Hsinchu, Taiwan TEL: 886-3-5984035 FAX: 886-3-5983301

Defom W-082 Aqueous Defoamer

DESCRIPTION

Defom W-082 is a hydrocarbon base aqueous defoamer, exhibit excellent antifoaming and defoaming effect.

TYPICAL PROPERTIES

These values are used as reference. For detailed product specifications, please contact our distributor or sales department.

Composition	: mixture of mineral oil and
	hydrophobic particle
Appearance	: opaque yellowish liquid
Non-volatile content	: 93 - 96%
Solvent	: water
Specific gravity	: 0.87 - 0.91

FEATURES

- Excellent antifoaming, defoaming and compatibity.
- Water dispersible.

APPLICATIONS

- latex
- aqueous adhesive
- paper pulp
- aqueous ink for corrugated paper

DOSAGE & USE

- 0.1 0.7% based on total formulation. Depend on the system and requirement.
- In corporation can be done at any stage of production. If post addition, stir to uniform.

PACKAGE

Net Weight: 25 kg

STORAGE

- Keep away from sources of ignition and heat.
- Keep container tightly closed in a dry and wellventilated place.
- Stored between 5°C and 40°C.
- Storage long-term, appearance may be seperation, stir before use.

SAFETY

- The product requires special care in handling.
- Avoid any eye and skin contact.
- For further information please check MSDS.

The data presented is the result of careful and extensive research. However, since the actual conditions under which the materials may be used are beyond our control, no warranty of any kind, expressed or implied, concerning the use of the products is made.