TOTAL PETROCHEMICALS POLYETHYLENE mPE

Page: 1/10

 Product :
 Revised :
 10/08/2011

 PETH-010
 Version (en) nr : 10.2
 Supersedes :
 15/07/2010

WARNING:

FOR STACKING

SECTION 7



1. Identification of the substance / mixture and of the company / undertaking

1.1. PRODUCT IDENTIFIER Polyethylene

Trade name TOTAL PETROCHEMICALS POLYETHYLENE mPE

SDS number PETH-010

Name of the product TOTAL mPE Lumicene

Chemical name ethylene - 1-hexene copolymer high, medium or low density

polyethylene

CAS number 25213-02-9

1. 2. RELEVANT IDENTIFIED USES OF THE SUBSTANCE AND USES ADVISED AGAINST

for more detailled information, see technical data sheet.

Recommended uses Recommended to professional users

1.3. DETAILS OF THE SUPPLIER OF SAFETY DATA SHEET

Trade name of the firm see below this page.

Email address: Petrochemicals.felr-sds@total.com

(Safety data sheet)

1.4. EMERGENCY TELEPHONE NUMBER Emergency call TOTAL PETROCHEMICALS:

for English speaking countries: +44 (0) 1235 239 670
for Europe (in local languages): + 33 1 49 00 00 49

• for Africa and Middle East: + 44 (0) 1235 239 671• for China:

+ 86 10 5100 3039

• for Asia Pacific (Hong-Kong, Singapore, Taiwan, Philippines, India, Vietnam, Sri Lanka, Japan, Korea, Malaysia, Indonesia, Thailand):

+ 65 3158 1074

Official advisory body The UK National Poisons Emergency number is 0870 600 6266

(Outside the UK: +44 870 600 6266)

NB: these services are only available to health professionals

IRL: National Poisons Information Centre

PO Box 1297, Beaumont Hospital, Beaumont Road

Dublin 9.

Telephone: +353 (01) 837 9964 / +353 (01) 809 2566

2. Hazards identification

2.1. Classification of the substance

EC-GHS (CLP) Not classified according to the regulation EC 1272/2008 (EC-GHS) and

ATP

TOTAL PETROCHEMICALS

a division of NV Petrofina SA rue de l'Industrie 52 Nijverheidsstraat B- 1040 BRUSSELS

BELGIUM

phone: +32 (0)2.288.91.11 - fax: +32 (0)2.288.33.69

www.totalpetrochemicals.com



Quick-FDS [16271-24964-22480-010675] - 2012-07-18 - 06:56:04

TOTAL PETROCHEMICALS POLYETHYLENE mPE

Page: 2/10

 Product :
 Revised :
 10/08/2011

 PETH-010
 Version (en) nr : 10.2
 Supersedes :
 15/07/2010

67/548/EEC & 1999/45/EC Not classified according to EEC directives 67/548/EEC (dangerous

substances) and 1999/45/EC (dangerous preparations).

<u>Main hazards</u> none to our knowledge

low risk for temperatures below 130 °C

Adverse human health effects

Inhalation fine dust may cause irritation of respiratory system and mucous.

if heated to more than 130°C, the product may form vapours or fumes which may cause irritation of respiratory tract and cause coughing and

sensation of shortness of breath.

Skin contact in contact with hot material, may cause severe thermal burns

Eye contact fine dust may cause irritation to ocular mucous.

Ingestion polyolefins are biologically inert.

Adverse environmental effects because of its structure, the product should not be dangerous for

aquatic life

non biodegradable

Adverse physicochemical effects combustible if exposed to flames.

flowing product can create electrical charge, resulting sparks may ignite dust or cause an explosion in some concentration ranges.

2.2. Label elements

EC-GHS (CLP) Not classified according to the regulation EC 1272/2008 (EC-GHS) and

ATP

Pictogram(s) -

WARNING:
FOR STACKING
PALLETS, SEE
SECTION 7



2.3. Other hazards no information available

3. Composition / information on ingredients

3.1. Substances (chemical name) Polyethylene ethylene - 1-hexene copolymer

Chemical formula (C2H4)x
CAS number 25213-02-9

EINECS or ELINCS number the product is a polymer, following the European regulation, registration

on the EINECS (European Inventory of Existing Commercial Chemical

Substances) inventory is not required.

EC-GHS (CLP) non required 67/548/EEC & 1999/45/EC non required

<u>Substances presenting a health hazard</u> none to our knowledge

Chemical family Olefinic polymer



a division of NV Petrofina SA rue de l'Industrie 52 Nijverheidsstraat B- 1040 BRUSSELS BELGIUM

phone: +32 (0)2.288.91.11 - fax: +32 (0)2.288.33.69

www.totalpetrochemicals.com



TOTAL PETROCHEMICALS POLYETHYLENE mPE

Page: 3/10

 Product :
 Revised :
 10/08/2011

 PETH-010
 Version (en) nr : 10.2
 Supersedes :
 15/07/2010

Additives Antioxidants and stabilisers : 0,7 % maximum

Pigments: from 0 to 8 %

4. First-aid measures

4.1. Description of first aid measures

Route of exposure

Inhalation exposure to spray, fumes and vapours produced by heated or burned

product:

bring patient into fresh air seek medical advice.

Skin contact exposure to splashing of hot product:

treat the affected part with cold water (by spraying or immersion). no attempt should be made to detach molten product adhering to the skin or to remove clothing attached with molten material, the injured body part would risk being pulled out; usually the layer detaches itself

after a few days.

in case of severe burns, seek hospital treatment

Eye contact exposure to splashing of hot product:

treat the eyes with cold water.

Seek specialist advice at hospital or medical centre fine dust may cause irritation to ocular mucous.

in case of irritation caused by fine dust: wash with copious volumes of

water, until the irritation disappears.

Ingestion ingestion during handling is not likely.

remove material from mouth do not induce vomiting.

Protective equipment for first-aiders wear suitable breathing equipment, in case of risk of exposure to

vapour or fumes.

4.2. Most important symptoms and effects, both acute and delayed

refer to § 11 for more details on effects.

4.3. Indication of any immediate medical attention and special treatment needed

no information available

5. Fire - fighting measures

Fire-class regulation A: Solid material fires, principally of organic nature, that burn with

incandescence

Technical measures stop the fire spreading.

call the fire brigade immediately. evacuate non-essential personnel

protective clothing, goggles and self-contained breathing equipment

should be made available for firemen.

5.1. Extinguishing media



a division of NV Petrofina SA rue de l'Industrie 52 Nijverheidsstraat B- 1040 BRUSSELS

phone: +32 (0)2.288.91.11 - fax: +32 (0)2.288.33.69

www.totalpetrochemicals.com



TOTAL PETROCHEMICALS POLYETHYLENE mPE

Page: 4/10

 Product :
 Revised :
 10/08/2011

 PETH-010
 Version (en) nr : 10.2
 Supersedes :
 15/07/2010

Suitable for minor fires: carbon dioxide (CO2) or powder,water

for more extensive fires : foam. water spray (mist) to cool the surfaces

exposed to the fire.

Not to be used do not use water jets (stick jets) for extinguishing fire since they could

help to spread the flames

5.2. Special hazards arising from the substance complete combustion, with an excess of oxygen forms: carbon dioxide

(CO2) and water vapour.

partial combustion, forms also: carbon monoxide (CO), soot and cracked products: aldehydes, ketones , Acetone , Acetaldehyde , Formaldehyde , Acrolein , hydrocarbons and volatile fatty acids

5.3. Advice for firefighters wear suitable breathing equipment, in case of risk of exposure to

vapour or fumes.

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel wear a suitable anti-dust respirator

where exposure is likely, protective clothing must be worn including

gloves

goggles/spectacles

For emergency responders wear suitable breathing equipment, in case of risk of exposure to

vapour or fumes.

6.2. Environmental precautions

do not dispose off this product into the environment

6.3. Methods and material for containment and cleaning up

on soil granules spilled on the floor can cause a risk of slipping on smooth

surfaces.

recover the spilled product by sweeping or suction; put it in containers

to facilitate its disposal.

dispose safely in accordance with local or national regulations.

on water prevent the spilled material from spreading.

if the material has been discharged into a stream or a sewerage system, inform the authorities of the possible presence of floating

materials.

clean up the water surface by creaming off debris from the top. refer to a specialist for waste disposal in a safe manner in accordance

with local or national regulations.

6.4. refer to points 8 and 13

7. Handling and storage

Important refer to any national measures that may be relevant.

7.1. Precautions for safe handling

TOTAL PETROCHEMICALS

ExESS®©



a division of NV Petrofina SA rue de l'Industrie 52 Nijverheidsstraat B- 1040 BRUSSELS BELGIUM

phone: +32 (0)2.288.91.11 - fax: +32 (0)2.288.33.69

www.totalpetrochemicals.com

TOTAL PETROCHEMICALS POLYETHYLENE mPE

Page: 5/10

 Product :
 Revised :
 10/08/2011

 PETH-010
 Version (en) nr : 10.2
 Supersedes :
 15/07/2010

Technical measures all pneumatic transport equipment must be electrically earthed.

avoid dust accumulation by use of filters in the pneumatic transport

equipment.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions store at ambient temperature and at atmospheric pressure in original

packaging (plastic or cardboard boxes) or in silo made of appropriate

material (aluminium, stainless steel, ...). do not store near highly flammable materials.

store away from heating source. avoid static electricity build up with

connection to earth.

store in dry, well-ventilated area.

prolonged storage preferably out of the sun or other sources of

radiation

Storage of pallets two pallets may be stacked on flooring in sound condition.

however, when the pictorial warning as shown on the top of the safety data sheet is affixed to the pallet, the pallet must never be placed either

on top of or below another pallet.

N.B. :here the term pallet includes both the pallet and its load. when pallets are stored in racks, it should be checked whether the

pallet is fit for stacking in the concerned racks

container

Suitable Polyethylene,paper bags,stainless steel

7.3. SPECIFIC USE(S) Recommended to professional users

refer to point 8

8. Exposure controls / personal protection

8.1. CONTROL PARAMETERS

OCCUPATIONAL EXPOSURE LIMIT

refer to any national measures that may be relevant.

inhalable dust particles:

US (ACGIH-2009): TLV-8h TWA: 10 mg/m³

UK: HSE EH40/2005:

Long-term exposure limit (8-hour TWA reference period): 10 mg/m³

(Total Inhalable Dust)

IRL(2002): OEL (8h): 10 mg/m³ (total inhalable)

ZA (2006): OEL (8h): 10 mg/m³ (inhalable particulate: PNOC)

respirable dust particles:

US (ACGIH-2009): TLV- 8h TWA: 3 mg/m³

UK: HSE EH40/2005:

Long-term exposure limit (8-hour TWA reference period): 4 mg/m³

(Respirable Dust)

IRL(2002): OEL (8h): 4 mg/m³ (respirable)

ZA (2006): OEL (8h): 5 mg/m³ (respirable particulate: PNOC)

8.2. EXPOSURE CONTROLS



TOTAL PETROCHEMICALS

a division of NV Petrofina SA rue de l'Industrie 52 Nijverheidsstraat B- 1040 BRUSSELS

BELGIUM

phone: +32 (0)2.288.91.11 - fax: +32 (0)2.288.33.69

www.totalpetrochemicals.com

TOTAL PETROCHEMICALS POLYETHYLENE mPE

Page: 6/10

Product: Revised: 10/08/2011 PETH-010 Version (en) nr: 10.2 Supersedes: 15/07/2010

Occupational exposure controls

Personal protection









Respiratory protection

in case of risk of overexposure to dust, vapour or fumes (during product processing), it is recommended that a local exhaust system is placed above the conversion equipment (a fume hood) and the working

area must be properly ventilated. wear a suitable anti-dust respirator recommended filter type: P1

Skin and body protection

where exposure is likely, protective clothing must be worn including

gloves

Eye protection

goggles/spectacles

Other personal protection

safety non-slip shoes in areas where spills or leaks can occur.

Industrial health measures

General use

local exhaust ventilation may be needed when working in a closed area

use working clothing.

do not store near food products.

When using, do not eat, drink or smoke.

Environmental exposure controls

handle in accordance with good industrial hygiene and safety

procedures

9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance powder or pellets

Physical state at 20°C solid

Colour translucent, white opaque or coloured

Odour odourless

Change in physical state at 1013 hPa

90 to 160 Melting range (°C) Flash point (ASTM D 1929)(°C) ± 340 Auto-ignition temperature (°C) > 350 **Explosion limits**

Lower 0.015 (for polymer dust < 63 μ m)

Min. ignition energy at 20°C (mJ) 63 Vapour pressure at 20°C (hPa) none

 (kg/m^3)



TOTAL PETROCHEMICALS a division of NV Petrofina SA

rue de l'Industrie 52 Nijverheidsstraat

B- 1040 **BRUSSELS BELGIUM**

phone: +32 (0)2.288.91.11 - fax: +32 (0)2.288.33.69

www.totalpetrochemicals.com

ExESS@©

TOTAL PETROCHEMICALS POLYETHYLENE mPE

Page: 7/10

 Product :
 Revised :
 10/08/2011

 PETH-010
 Version (en) nr : 10.2
 Supersedes :
 15/07/2010

Density, mass at 20°C (kg/m³) 910 - 990 (ISO 1183)

Solubility in water at 20°C (mg/l) insoluble

pH value (concentrated product) not applicable

Viscosity (mm²/s) not applicable

9.2. OTHER INFORMATION no information available

10. Stability and reactivity

10.1. REACTIVITY the product is combustible if heated above the flash point.

10.2. CHEMICAL STABILITY stable under normal operating conditions of storage, handling and use

10.3. POSSIBILITY OF HAZARDOUS REACTIONS

dust may form an explosive mixture with air, ignited by sparks or

sources of ignition.

10.4. CONDITIONS TO AVOID avoid proximity or contact with flames or sparks

it is recommended not to heat at a temperature higher than 320 °C

10.5. INCOMPATIBLE MATERIALS avoid contact with strong acids

halogens

10.6. HAZARDOUS DECOMPOSITION PRODUCTS

complete combustion, with an excess of oxygen forms: carbon dioxide

(CO2) and water vapour.

partial combustion, forms also: carbon monoxide (CO), soot and

cracked products: aldehydes, ketones

Advice to prevent explosion avoid dust accumulation by use of filters in the pneumatic transport

equipment.

thoroughly ventilate the working place.

all conductive materials must be electrically earthed.

in case of pneumatic alimentation, feed the extruders by aspiration, use

preferably nitrogen as carrier gas

11. Toxicological information

11.1. Information on toxicological effects

ACUTE TOXICITY polyolefins are biologically inert.

<u>Ingestion</u> because of its composition, the product should be considered as

practically not harmful

LOCAL EFFECT

Inhalation dust may cause irritation of respiratory system.

if heated to more than 130°C, the product may form vapours or fumes which may cause irritation of respiratory tract and cause coughing and

sensation of shortness of breath.

Skin contact because of its composition, the product should be considered



TOTAL PETROCHEMICALS

a division of NV Petrofina SA rue de l'Industrie 52 Nijverheidsstraat B- 1040 BRUSSELS

BELGIUM

phone: +32 (0)2.288.91.11 - fax: +32 (0)2.288.33.69

www.totalpetrochemicals.com

TOTAL PETROCHEMICALS POLYETHYLENE mPE

Page: 8/10

 Product :
 Revised :
 10/08/2011

 PETH-010
 Version (en) nr : 10.2
 Supersedes :
 15/07/2010

practically as not irritating

in contact with hot material, may cause severe thermal burns thermal decomposition products are produced at elevated

temperatures and these may be irritating

Eye contact because of its composition, the product should be considered

practically as not irritating

fine dust may cause irritation to ocular mucous.

splashing of molten droplets causes ocular tissue burns. thermal decomposition products are produced at elevated

temperatures and these may be irritating

SPECIFIC EFFECTS polyolefins are biologically inert.

no particular preoccupation for man

(Genotoxicity, carcinogenicity, reproductive toxicity)

12. Ecological information

Information on ecological effects avoid losses to the environment whenever possible.

12.1. TOXICITY because of its structure, the product should not be dangerous for

aquatic life

12.2. PERSISTENCE AND DEGRADABILITY persistent in the environment

Biodegradation this substance is slowly biodegradable

BOD 5 (gO2/g) below the detection limit

12.3. BIOACCUMULATIVE POTENTIAL potential bioaccumulation of the product in environment is very low

12.4. MOBILITY

water / air there is a slow loss by evaporation

volatile organic compound (VOC) content of this product is < at 0.3 %

weight

soil and sediments because of its physico-chemical properties, the product has a low soil

mobility

water the product, in cases of accidental discharge, floats on the surface, is

insoluble and its evaporation into air is practically nil

12.5. Results of PBT and vPvB assessment non required

12.6. OTHER ADVERSE EFFECTS non required



TOTAL PETROCHEMICALS

a division of NV Petrofina SA rue de l'Industrie 52 Nijverheidsstraat B- 1040 BRUSSELS

phone: +32 (0)2.288.91.11 - fax: +32 (0)2.288.33.69

www.totalpetrochemicals.com

TOTAL PETROCHEMICALS POLYETHYLENE mPE

Page: 9/10

 Product :
 Revised :
 10/08/2011

 PETH-010
 Version (en) nr : 10.2
 Supersedes :
 15/07/2010

13. Disposal considerations

13.1. Waste treatment methods according to local regulations.

authorized disposal as refuse for reprocessing

do not dispose off by means of sinks, drains or into the immediate

environment

may be used as fuel in suitably designed installations.

incinerate with household refuse in a municipal solid waste incinerator

plan.

Industrial waste number EC 07 02 13, 16 01 19, 17 02 03 & 20 01 39: plastics

API (Association of Plastic Industry) Code 2: HDPE: high density Polyethylene

14. Transport information

Road (ADR) / Rail (RID) Not restricted for transport.

UN Number not applicable

Inland waterways (ADN)Not restricted for transport.

Marine (IMO) Not restricted for transport.

Air transport (ICAO / IATA)

Not restricted for transport.

15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Germany

Wassergefährdungsklasse NWG: non-hazardous to waters

Registration These registration entries are for polymers only. For additives, please

refer to TOTAL PETROCHEMICALS who will provide the necessary

certification

the product is a polymer, following the European regulation, registration on the EINECS (European Inventory of Existing Commercial Chemical

Substances) inventory is not required.

listed on the United States TSCA (Toxic Substances Control Act)

inventory

listed on the Canadian DSL (Domestic Substances List) inventory. listed on the Japanese ENCS (Existing & New Chemical Substances)

inventory

listed on the AICS (the Australian Inventory of Chemical Substances).

TOTAL PETROCHEMICALS

a division of NV Petrofina SA rue de l'Industrie 52 Nijverheidsstraat B- 1040 BRUSSELS BELGIUM

phone: +32 (0)2.288.91.11 - fax: +32 (0)2.288.33.69

www.totalpetrochemicals.com

TOTAL PETROCHEMICALS POLYETHYLENE mPE

Page: 10/10 Revised: 10/08/2011

PETH-010 Version (en) nr : 10.2 Supersedes : 15/07/2010

listed on the Korean ECL (Existing Chemical List) inventory.

listed on the Filipino PICCS (Philippine Inventory of Chemicals and

Chemical Substances) inventory.

listed on the swiss (liste des toxiques IGS/ IGS Giftliste 2003-2004)

inventory

listed on the People's Republic of China register: CRC-SEPA (Chemical Registration Center for Chinese State Environmental

Protection Administration)

15.2. Chemical safety assessment non required

16. Other information

Product:

Training advice The use of this product requires specific training.

The user must receive all product information in order to handle the

product safely

(personal protection equipment and best practice standards)

Further information no information available

Safety data sheet conforms to the Regulation (EU) N° 1907/2006

This information applies to the PRODUCT AS SUCH and conforming to specifications of TOTAL PETROCHEMICALS.

In case of formulations or mixtures, it is necessary to ascertain that a new danger will not appear.

The information contained is based on our knowledge of the product, at the date of publishing and it is given quite sincerely. However the revision of some data is in progress.

Users are advised of possible additional hazards when the product is used in applications for which it was not intended. This sheet shall only be used and reproduced for prevention and security purposes.

The references to legislative, regulatory and codes of practice documents cannot be considered as exhaustive. It is the responsibility of the person receiving the product to refer to the totality of the official documents concerning the use, the possession and the handling of the product.

It is also the responsibility of the handlers of the product to pass on to any subsequent persons who will come into contact with the product. (usage, storage, cleaning of containers, other processes) the totality of the information contained within this safety data sheet and necessary for safety at work, the protection of health and the protection of environment.

The (*) indicate the changes made with respect to the previous version.



TOTAL PETROCHEMICALS

a division of NV Petrofina SA rue de l'Industrie 52 Nijverheidsstraat B- 1040 BRUSSELS BEI GIUM

phone: +32 (0)2.288.91.11 - fax: +32 (0)2.288.33.69

www.totalpetrochemicals.com