

## Lead based compound stabilizer (PVC Profile)

### Introduction:

**JX-03** series products are lead based compound stabilizer containing light Lead based compound, antioxidant, internal and external lubricants, which is applicable for U-PVC profile extrusion. It is irregular flake or granule and dust-free. It contains proper composite antioxidant and macromolecule auxiliaries, which can obviously improve the outdoor using performance of plastic profile products, and completely adapt for all kinds of PVC profile production under the GB/T 8814-2004 standard.



### Product performance:

**JX-03** series products have good thermo stability and processing performance, strong anti-separation performance, reasonable formulation, effectively resistant to climate, strong weld angle and low temperature impact performance. It is completely adapt for different processing extrusion equipments at home or abroad.

### Specification:

Item \ Type	JX-03	JX-03S-5	JX-03S-9	JX-03S-6	JX-S308	JX-308L	JX-T303
Appearance	White /yellow, Flake						
Lead oxide content, %	35±1.0	20±1.0	22±1.0	34±1.0	48±1.0	35±1.0	52±1.0
Initial melting point, °C	>55	>55	>55	>55	>55	>55	>55
Heating loss, %	<2	<2	<2	<2	<2	<2	<2
Reference feed rate (phr)	4.6-5.0	4.8-5.6	4.8-5.0	4.6-5.0	3.6-3.8	3.6-3.8	3.5-4.0

### Package and storage:

Packed in weaved bag, lined with a PE bag, 25kg in weight. It can be stored in a cool and dry place with good ventilation. The expiring date is 12 months from the date of produced.